

Performance of the e2v 1.2 GPixel cryogenic camera for the J-PAS 2.5m survey telescope

M S Robbins^{*a}, M Bastable^a, A Bates^a, S Eames^a, G Fenemore-Jones^a, G Haddow^a, P R Jordan^a, B Lane^a, A Marin-Franch^b, J Mortimer^a, I Palmer^a, N Puttay^a, R Renshaw^a, M Smith^a, A Taylor^a, K Taylor^c, J Tearle^a, P Weston^a, P Wheeler^a, J Worley^a

^a e2v, Waterhouse Lane, Chelmsford, Essex, CM1 2QU, UK; ^b Centro de Estudios de Física del Cosmos de Aragon, Plaza San Juan 1 piso 2, 44001 Teruel, Spain; ^c Universidade de Sao Paulo, IAG, Rua do Matao, 1226, Sao Paulo, 05508-900, Brazil

J-PAS CryoCam

Introduction

- J-PAS - Javalambre Physics of the accelerating universe Astronomical Survey
- J-PAS is a 5 year wide-area astrophysical mapping survey which primarily aims to explore dark energy in the universe
- The dedicated 2.5m telescope (built in Teruel, Spain) will use 56 narrow band optical filters to build up a 3-D map of the universe by studying red-shifts
- e2v are supplying the 1.2 GPixel camera which is mounted on the back of the T250 telescope


<http://www.j-pas.org/>



Overview

Presenting a review the factory performance of the e2v JPAS CryoCam following AIVT

- Overview of Cryocam
- The Opto-Mechanical Sub-System
 - Opto-Mechanical Description
 - Geometric Verification
- The Instrument Control and Support Sub-System
 - Sub-System description
 - Thermal Performance
 - Vacuum Performance
- Detector Control Sub-System
 - Electronics overview
 - Electrical Performance
 - CCD Level
 - Module Level
 - System Level
- Conclusion




J-PAS CryoCam

Overview of CryoCam




J-PAS CryoCam

Overview of CryoCam



J-PAS CryoCam


Overview of CryoCam



J-PAS CryoCam


The Opto-Mechanical Sub-System

- Assembly housed within custom vacuum cryostat
- LN₂ passed through a Cu ring and changes phase
- Cold plate attached to Cu ring with Cu straps
- Initially evacuated with a Turbo Pump
- Vacuum held with a sorption pump





J-PAS CryoCam

The Opto-Mechanical Sub-System – Geometric Verification



J-PAS CryoCam

The Opto-Mechanical Sub-System – Geometric Verification





The focal plane inside the cryostat plane and flatness measurements made at $-110\text{ }^{\circ}\text{C}$ showing the 14 science devices, 8 wavefront and 4 autoguide CCDs.

Flatness achieved - **27 μm peak to valley** for (spec 40μm target 30μm)


J-PAS CryoCam

The Instrument Control and Support Sub-System

- Pair of LN2 Dewars mounted on telescope fork
- Temperature control implemented through PLC system
- Controls rate of flow of GN2 flowing from cryostat
- No heaters in cold plate assembly
- PID control employed
- Time constant ~ 3.5 hours




The Instrument Control and Support Sub-System – Thermal Performance



The control temperature and the Dewar fill level


J-PAS CryoCam

The Instrument Control and Support Sub-System – Thermal Performance



The control temperature and the radiative heat load on the cold plate


The Instrument Control and Support Sub-System – Vacuum Performance



Sorption pump only – no cryostat conditioning

J-PAS CryoCam

Detector Control Sub-System



J-PAS CryoCam

Detector Control Sub-System – CCD Level Performance


- The CCDs supplied as high grade devices
- All CCD testing undertaken using dedicated production test equipment
- CCDs tested for noise, responsivity, linearity, QE, CTE, dark signal, PRNU, DSNU, defects....

14xCCD290-99 Science Devices

9kx9k full frame

16 differential outputs


630 kHz and 400 kHz



8xCCD44-82 Wavefront

2kx2k frame transfer


100x100 window at 1 fps



4xCCD47-20 Autoguide

1kx1k frame transfer


50x50 window at 4 fps



J-PAS CryoCam


Detector Control Sub-System – Module Level Performance

- Each of the 22 electronics modules bench tested and tested with associated test devices.
- Test device is mounted in a “mini” cryostat
- Tested for functionality, noise, linearity, gain, CTE



A wavefront module being tested



Detector Control Sub-System – Module Level Performance



J-PAS CryoCam



Detector Control Sub-System – System Level Performance

- System level performance assessed for noise, cross talk and functionality




J-PAS CryoCam

Detector Control Sub-System – System Level Performance



Detector Control Sub-System – System Level Performance


- The measured system level noise for all science devices operating in parallel.



- Inter channel and inter device cross talk less than 106 dB

J-PAS CryoCam

Detector Control Sub-System – System Level Performance



System noise from a single science output measured over a 6 day period. All devices are operating and a noise measurement is made every 25 seconds.

J-PAS CryoCam

Conclusions

- The e2v CryoCam has completed factory acceptance tests and passed the System Acceptance Review 😊😊😊
- From the final critical design review it has taken 15 months to complete the complex AIVT phases of the programme.
- System level tests have verified performance against all key aspects of the customer requirements
- Key features include
 - Precision construction and metrology to meet geometrical/mechanical specifications
 - e.g. exceeding the focal plane flatness spec to achieve 27 um p-v cryogenic flatness
 - Validated differential digital correlated double sampling signal chain
 - providing read-noise that exceeded guaranteed specification
 - Custom cryogenic/vacuum system for reliable and low maintenance operation
- We have demonstrated that the supply of a complex, high performance camera system can be undertaken by a commercial organisation. This includes use of rigorous quality systems, delivering guaranteed performance levels, as well as being to an agreed price and schedule

J-PAS CryoCam



Acknowledgements

Many people at e2v, in addition to the core e2v J-PAS team, have contributed to the successful delivery of this program.

I would also like to thank the J-PAS collaboration and those supporting the collaboration for valuable interactions throughout the project.



**WE PARTNER WITH OUR CUSTOMERS TO IMPROVE,
SAVE AND PROTECT PEOPLE'S LIVES**

**OUR INNOVATIONS LEAD DEVELOPMENTS IN COMMUNICATIONS, AUTOMATION,
DISCOVERY, HEALTHCARE AND THE ENVIRONMENT**