

Orbis⁴⁷

IC-47-12288-00-R (BSI / FSI)

Imaging Sensors



Key Features

- » Very high resolution
- » CCD on CMOS architecture
- » 4 Multispectral Bands (B1-B4) and 2 Panchromatic bands (P1 and P2, with half pixel offset)
- » Selectable TDI stages: B1-B4: 2, 4, 8, 16, 24, 32, P: 4, 8, 16, 32, 48, 64, 96, 128
- » User selectable outputs: 8 primary + 8 redundant
- » Back thinned – back illuminated technology
- » Front side illumination options
- » Integrated multispectral filters
- » On-chip integration / easy to integrate
- » Anti-blooming
- » Bi-directional
- » Fully digital outputs – no focal plane ADCs required
- » Redundancy: Ramp Generator, Global Counter, Serializers
- » Radiation tolerance:
 - » ≥ 20 krad (Si), Co^{60} (TID)
 - » No destructive latch-up (SEL) ≥ 75 MeV/mg/cm²

Typical Applications

- » Earth observation
- » Remote sensing
- » Aerial reconnaissance

Options suited to New Space applications available upon request.

Teledyne Imaging has extensive heritage in providing standard and customised image sensors for space applications. Please discuss any requirements for customised variants to meet your needs.

12k Pixel Bidirectional, Multispectral Charge Domain TDI CMOS Sensor with Filters

Teledyne Imaging's Orbis⁴⁷ image sensor combines charge domain TDI CCD functionality on a CMOS chip, offering the best of both technologies. With on-chip clock drivers and ADCs, this sensor offers a true integrated solution. This is a front-side illuminated (FSI) sensor. Backside illuminated (BSI) version is also feasible. These TDI CMOS image sensor includes four filtered multispectral bands and two panchromatic bands, all in a single integrated CMOS die and package. With a horizontal resolution of 3072 for each multispectral band and 12288 for each panchromatic band along with lateral anti-blooming (LAB), and continuous vertical clocking, the sensor guarantees exceptional images with very high MTF. With $7\mu\text{m} \times 7\mu\text{m}$ (P) and $28\mu\text{m} \times 28\mu\text{m}$ (B1-B4) pixels this sensor provides extraordinary images. Two panchromatic bands with half pixel ($3.5\mu\text{m}$) offset, in both horizontal and vertical directions, allow super-resolution imaging to further enhance the resolution.


Focal plane arrays (FPA) are also available with 24k and 36k pixels.

	2020	2021	2022	2023	2024
Orbis ⁴⁷	TRL8	TRL9	TRL9	TRL9	TRL9


Performance Specifications	
Number of pixels	P: 12288 MS: 3072
Channels	P: 2 MS: 4
Pixel size	P: $7\mu\text{m} \times 7\mu\text{m}$ MS: $28\mu\text{m} \times 28\mu\text{m}$
Max. line rate	P: 34.5 kHz MS: 8.625 kHz
CTE per transfer	≥ 0.99995
Fixed pattern noise	$\leq 4\%$ Sat (peak-to-peak)
Average dark current @ 25°C	≤ 4 nA/cm ²
Full Well Capacity	P: 31k e- MS: 124k e-
Noise RMS	P: ≤ 16 e- MS: ≤ 55 e-
Read-out speed at max. line rate	Typical: 2.2Gb/s via CML interface @ 55MHz input master clock
On-chip ADC resolution	12 bits
Dynamic range	≥ 65 dB
Power dissipation	Typical: ≤ 6 W

* Datasheets available upon request

ARCHITECTURE



TYPICAL QUANTUM EFFICIENCY



Information subject to change – values typical unless otherwise stated.

Europe
Essex, United Kingdom
+44 (0) 1245 493 493

Canada
Waterloo, Ontario
+00 (1) 519-886-6000

email:
TDI_Sensorsystems@Teledyne.com